



Safety Data Sheet

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

Brake and Clutch Fluid DOT 3, 4

Product Use: Brake Fluid

Product Number(s): 510662, 510663

Company Identification

Chevron Lubricants Vietnam Limited
Block F4 - Dinh Vu Industrial Zone - An Hai
Hai Phong
Vietnam

Transportation Emergency Response

Chevron Emergency Information Center: Located in the USA. International collect calls accepted. (800) 231-0623 or (510) 231-0623

Health Emergency

Chevron Emergency Information Center: Located in the USA. International collect calls accepted. (800) 231-0623 or (510) 231-0623

Product Information

email : CLVLTech@chevron.com
Product Information: +84-4-37332545
Fax number: +84-4-37332555

SECTION 2 COMPOSITION/ INFORMATION ON INGREDIENTS

COMPONENTS	CAS NUMBER	AMOUNT
Triethylene glycol monobutyl ether	143-22-6	15 - 50 %weight
Diethylene glycol	111-46-6	10 - 30 %weight
Diethylene glycol monobutyl ether	112-34-5	0 - < 3 %weight
Diethylene glycol monomethyl ether	111-77-3	0.1 - 1 %weight

SECTION 3 HAZARDS IDENTIFICATION

CLASSIFICATION: Eye irritation: Category 2A. Reproductive toxicant: Category 2. Acute dermal toxicant: Category 5.



Signal Word: Warning

Health Hazards: Causes serious eye irritation (H319). Suspected of damaging fertility or the unborn child (H361). May be harmful in contact with skin (H313)

PRECAUTIONARY STATEMENTS:

Prevention: Obtain special instructions before use (P201). Do not handle until all safety precautions have been read and understood (P202). Wear protective gloves/protective clothing/eye protection/face protection (P280). Wash thoroughly after handling (P264).

Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing (P305+P351+P338). Call a POISON CENTER or doctor/physician if you feel unwell (P312). IF exposed or concerned: Get medical advice/attention (P308+P313). If eye irritation persists: Get medical advice/attention (P337+P313).

Storage: Store locked up (P405).

Disposal: Dispose of contents/container in accordance with applicable local/regional/national/international regulations (P501).

SECTION 4 FIRST AID MEASURES

Eye: Flush eyes with water immediately while holding the eyelids open. Remove contact lenses, if worn, after initial flushing, and continue flushing for at least 15 minutes. Get immediate medical attention.

Skin: Wash skin with water immediately and remove contaminated clothing and shoes. Get medical attention if any symptoms develop. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

Ingestion: No specific first aid measures are required. Do not induce vomiting. As a precaution, get medical advice.

Inhalation: No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.

Note to Physicians: In an accident involving high-pressure equipment, this product may be injected under the skin. Such an accident may result in a small, sometimes bloodless, puncture wound. However, because of its driving force, material injected into a fingertip can be deposited into the palm of the hand. Within 24 hours, there is usually a great deal of swelling, discoloration, and intense throbbing pain. Immediate treatment at a surgical emergency center is recommended.

SECTION 5 FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

Unusual Fire Hazards: Leaks/ruptures in high pressure system using materials of this type can create a fire hazard when in the vicinity of ignition sources (eg. open flame, pilot lights, sparks, or electric arcs).

PROTECTION OF FIRE FIGHTERS:

Fire Fighting Instructions: This material will burn although it is not easily ignited. See Section 7 for proper handling and storage. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

Combustion Products: Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Protective Measures: Eliminate all sources of ignition in vicinity of spilled material.

Spill Management: Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

Reporting: Report spills to local authorities as appropriate or required.

SECTION 7 HANDLING AND STORAGE

Precautionary Measures: DO NOT USE IN HIGH PRESSURE SYSTEMS in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed. Do not get in eyes, on skin, or on clothing. Do not get in eyes. Do not taste or swallow. Wash thoroughly after handling. Keep out of the reach of children.

Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures.

Container Warnings: Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly

returned to a drum reconditioner or disposed of properly.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see Section 3), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

ENGINEERING CONTROLS:

Use in a well-ventilated area.

PERSONAL PROTECTIVE EQUIPMENT

Eye/Face Protection: Wear protective equipment to prevent eye contact. Selection of protective equipment may include safety glasses, chemical goggles, face shields, or a combination depending on the work operations conducted.

Skin Protection: Wear protective clothing to prevent skin contact. Selection of protective clothing may include gloves, apron, boots, and complete facial protection depending on operations conducted.

Suggested materials for protective gloves include: Butyl, Natural rubber, Polyethylene, Polyvinyl Chloride (PVC or Vinyl).

Respiratory Protection: No respiratory protection is normally required.

Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate protection.

Occupational Exposure Limits:

Component	Country/ Agency	TWA	STEL	Ceiling	Notation
Diethylene glycol monobutyl ether	ACGIH	10 ppm (weight)	--	--	--

Consult local authorities for appropriate values.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Attention: the data below are typical values and do not constitute a specification.

Color: Colorless to amber

Physical State: Liquid

Odor: Faint or Mild

Odor Threshold: No data available

pH: No data available

Vapor Pressure: <200 Pa Maximum @ 20 °C (68 °F)

Vapor Density (Air = 1): No data available

Boiling Point: 206°C (402.8°F) Minimum

Solubility: Miscible

Freezing Point: Not Applicable

Melting Point: <-50°C (-58°F) Maximum

Density: 1.02 kg/l - 1.07 kg/l @ 20°C (68°F)

Viscosity: 5 mm²/s @ 20°C (68°F) Minimum

Evaporation Rate: No data available

Octanol/Water Partition Coefficient: <2 Maximum

FLAMMABLE PROPERTIES:

Flashpoint: > 94 °C (> 201 °F) Minimum

Autoignition: > 300 °C (> 572 °F)

Flammability (Explosive) Limits (% by volume in air): Lower: No data available Upper: No data available

SECTION 10 STABILITY AND REACTIVITY

Reactivity: May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Chemical Stability: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Incompatibility With Other Materials: Not applicable

Hazardous Decomposition Products: None known (None expected)

Hazardous Polymerization: Hazardous polymerization will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

IMMEDIATE HEALTH EFFECTS

Eye: Contact with the eyes causes severe irritation. Symptoms may include pain, tearing, reddening, swelling and impaired vision.

Eye Irritation: The eye irritation hazard is based on evaluation of data for product components.

Skin: Skin contact may cause drying or defatting of the skin. High-Pressure Equipment Information: Accidental high-velocity injection under the skin of materials of this type may result in serious injury. Seek medical attention at once should an accident like this occur. The initial wound at the injection site may not appear to be serious at first; but, if left untreated, could result in disfigurement or amputation of the affected part.

Symptoms may include pain, itching, discoloration, swelling, and blistering. Contact with the skin is not expected to cause an allergic skin response. Not expected to be harmful to internal organs if absorbed through the skin.

Acute Dermal Toxicity: The acute dermal toxicity hazard is based on evaluation of data for product components.

Skin Irritation: The skin irritation hazard is based on evaluation of data for product components.
Skin Sensitization: The skin sensitization hazard is based on evaluation of data for product components.

Ingestion: Not expected to be harmful if swallowed.
Acute Oral Toxicity: The acute oral toxicity hazard is based on evaluation of data for product components.

Inhalation: Not expected to be harmful if inhaled.
Acute Inhalation Toxicity: The acute inhalation toxicity hazard is based on evaluation of data for product components.
Acute Toxicity Estimate: Not Determined

DELAYED OR OTHER HEALTH EFFECTS:

Reproduction and Birth Defects: Contains material that may cause adverse reproductive effects if swallowed based on animal data.
See Section 11 for additional information. Risk depends on duration and level of exposure.

ADDITIONAL TOXICOLOGY INFORMATION:

This product contains diethylene glycol (DEG). The estimated oral lethal dose is about 50 cc (1.6 oz) for an adult human. DEG has caused the following effects in laboratory animals: liver abnormalities, kidney damage and blood abnormalities. It has been suggested as a cause of the following effects in humans: liver abnormalities, kidney damage, lung damage and central nervous system damage.

SECTION 12 ECOLOGICAL INFORMATION

ECOTOXICITY

This material is not expected to be harmful to aquatic organisms.
The product has not been tested. The statement has been derived from the properties of the individual components.

MOBILITY

No data available.

PERSISTENCE AND DEGRADABILITY

This material is expected to be readily biodegradable. The biodegradability of this material is based on an evaluation of data for the components or a similar material.
The product has not been tested. The statement has been derived from the properties of the individual components.

POTENTIAL TO BIOACCUMULATE

Bioconcentration Factor: No data available.
Octanol/Water Partition Coefficient: <2 Maximum

SECTION 13 DISPOSAL CONSIDERATIONS

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by international, country, or local laws and regulations.

SECTION 14 TRANSPORT INFORMATION

The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

DOT Shipping Description: NOT REGULATED AS A HAZARDOUS MATERIAL UNDER 49 CFR

IMO/IMDG Shipping Description: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER THE IMDG CODE

ICAO/IATA Shipping Description: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER ICAO

SECTION 15 REGULATORY INFORMATION

REGULATORY LISTS SEARCHED:

- 01-1=IARC Group 1
- 01-2A=IARC Group 2A
- 01-2B=IARC Group 2B

No components of this material were found on the regulatory lists above.

CHEMICAL INVENTORIES:

All components comply with the following chemical inventory requirements: AICS (Australia), DSL (Canada), EINECS (European Union), ENCS (Japan), IECSC (China), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States).

SECTION 16 OTHER INFORMATION

REVISION STATEMENT: This revision updates the following sections of this Material Safety Data Sheet: 1-16

Revision Date: April 25, 2017

ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

TLV - Threshold Limit Value	TWA - Time Weighted Average
STEL - Short-term Exposure Limit	PEL - Permissible Exposure Limit
	CAS - Chemical Abstract Service Number
ACGIH - American Conference of Governmental Industrial Hygienists	IMO/IMDG - International Maritime Dangerous Goods Code

API - American Petroleum Institute	MSDS - Material Safety Data Sheet
CVX - Chevron	NFPA - National Fire Protection Association (USA)
	NTP - National Toxicology Program (USA)
IARC - International Agency for Research on Cancer	

Prepared according to the Law on Chemicals no. 6/2008/QH12 by Chevron Energy Technology Company, 6001 Bollinger Canyon Road, San Ramon, CA 94583.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.